

SpryStep® OA Knee

U33601

Contact Information	Ordering Clinician
☐ Clinician ☐ Fitter/Assistant/Tech ☐ Other:	☐ CPO ☐ CP ☐ Other:
Name:	Name:
Email: Phone:	Email: Phone:
Billing & Shipping PO#:	
Billing Account#:	Shipping Address:
Shipping Account#:	City: State: Zip:
Shipping Preference	AM
Patient Information	☐ BK Brace
Fit Date: Patient ID:	Tibia Straps □ No straps □ 1 strap □ 2 straps
Age	Brace Rigidity/ Stiffness
Weight □ Lbs. □ Kg. Height □ in. □ cm.	For larger and heavier framed patients- increased rigidity / stiffness is recommended
Leg: □ Left □ Right	☐ Level 1 (default) ☐ Level 2 (medium) ☐ Level 3 (high)
Diagnosis: (ex: Ligament laxity, ROM limitations, etc.)	Femoral shell length
	☐ 7 in 175mm (default) ☐ -1 in 150mm ☐ +1 in 200mm (Loadshifter not available for this length)
Compartment: ☐ Unload Medial ☐ Unload Lateral	Femoral shell configuration
Measurement Data	☐ Anterior ☐ Posterior
These measurements are required to check the accuracy of the patient model submitted, a patient model must be provided for fabrication (scan).	Tibial shell length
111 /	☐ 7 in 175mm (default) ☐ -1 in 150mm ☐ +1 in 200mm
Proximal circumference 7 in / 175mm above mid-patella	*Custom length requests require pre-fabrication consultation, additional charges will be applied.
Medial-Lateral Knee Width	Tibial shell configuration
(not circumference) at knee center	☐ Anterior ☐ Posterior Full Shell
Distal circumference 7 in / 175mm below mid-patella	Options Please select only one of the following selections
Brace Configuration NB by default: riveted anchor tabs + d-rings + 1/4" padding + condylar pads + 2 additional thicker condylar pads + synergistic suspension strap	 ☐ Full Shell* ☐ C/S Package (not available with FullShell) ☐ Combined Instability Strap(PCL) not available with Full Shell
Hinge (Extension stop kit inclued with hinges)	Accessories
☐ TM5 Aluminum with Loadshifter	☐ Spooner Patella Stabilizing Attachment*
☐ TM5 Aluminum without Loadshifter, Correction built into the frame:° ☐ Varus ☐ Valgus	☐ Brace cover (pull-on style)* ☐ Cotton Undersleeve 18 in (46cm)*
☐ TM5 Stainless without Loadshifter, Correction built into the frame:° ☐ Varus ☐ Valgus	 □ Neoprene Undersleeve 18 in (46cm)* □ CS wrap* □ Anti-migration silicon infused strap pads*
Optional Hinge Accessories	
☐ Flexion stop kit* ☐ Extension assist bands/posts*	Comments:

*Indicates additional charges apply